



TECHNICAL BULLETIN

YELLOW SUPREME PAD

PRODUCT: PDR0900N Yellow Supreme Polish Pad

PRIMARY USE:

Yellow Supreme Polish pad for polishing of all plastic lens materials during ophthalmic manufacturing.

DESCRIPTION:

3" 7 leaf Yellow Supreme polish pad. High strength textile carrier coated on one side with precision cut rayon flock. Textile side of material is coated with natural rubber pressure sensitive adhesive for firm, temporary positioning.

LINER:

Tan densified kraft paper, poly coated on one side.

Recommended Times and Pressure:

LOH	4-6 minutes @ .25 to .35 bar
Coburn / Optek	4-6 minutes @ 18-20 psi

TYPICAL PHYSICAL PROPERTIES:

1. Thickness:

Pad Material & Adhesive.....	.033 " / .84mm (+/- .002")
Liner.....	4.8 mils (+/- 0.2 mils)

2. Peel Adhesion:

PSTC #3	
Lined side.....	28 oz./in. (+/- 5 oz)

3. Dynamic Shear:

(@ 12"/Min.)	
Lined side.....	45 lbs/in. (+/- 6 lbs)

PACKAGING:

250 per roll with plastic shrink wrap. Labeled in core with lot number information

No warranties are made in this Bulletin. All information, recommendations and descriptive material concerning DAC products are based upon research which is believed to be reliable but shall not constitute a warranty. Accordingly, all DAC products are sold with the understanding that purchaser will be solely responsible for determining the suitability of the materials for any purpose.